TRACO POWER

AC/DC Industrial Power Supply

TXO 60 Series, 60 Watt

- **Compact open frame power supply with pin connectors**
- **Universal input range 85 to 264 VAC**
- **Convection cooled (no-fan)**
- **Operating temperature range: -20°C to +70°C**
- **Internal EN55032 class B filter**
- **Short circuit, overvoltage and overload protection**
- **IEC/EN/UL 62368-1 safety approvals**
- **Compliance to EN 61000-3-2**
- **3-year product warranty**



UL 62368-1 IEC 62368-1

The TXO 60 is a compact 60 Watt AC/DC open frame module with reinforced I/O isolation designed for a wide range of cost sensitive applications. Excellent temperature behaviour allows full load operation from -20°C to +50°C while going up to +70°C with derating. The TXO 60 series features short circuit protection, over current limitation and overvoltage protection and complies with European EMC standards and the Low Voltage Directive (LVD).

Models

Order Code	Output Power max.	Output Voltage nom.	Output Current max.	Efficiency typ.
TXO 60-112-J	60 W	12 VDC	5'000 mA	85 %
TXO 60-115-J		15 VDC	4'000 mA	85 %
TXO 60-124-J		24 VDC	2'500 mA	85 %
TXO 60-148-J		48 VDC	1'250 mA	85 %

Options

TCI 130-DC	- Optional Cable: www.tracopower.com/overview/tci130-dc
TCI-AC1	- Optional Cable: www.tracopower.com/overview/tci-ac1
on demand (backorder with MOQ non stocking item)	- Optional model with 36 VDC and 1'670 mA - Optional model with 56 VDC and 1'070 mA

Downloaded from Arrow.com.

Input Specifications

Input Voltage	- AC Range	Operational Range:	85 - 264 VAC (Full Range)
		Rated Range:	100 - 240 VAC (Full Range)
	- DC Range	Operational Range:	120 - 370 VDC (Designed for, no certification)
		Polarity:	irrelevant
Input Frequency		Operational Range:	47 - 63 Hz
		Certified:	50/60 Hz
Power Consumption	- No load & Vin = 230 VAC		100 mW max. (Ready to meet ErP directive)
	- No load & Vin = 115 VAC		100 mW max.
Input Current	- Full load & Vin = 230 VAC		750 mA max.
	- Full load & Vin = 115 VAC		1'250 mA max.
Input Inrush Current	- At 230 VAC		80 A max.
	- At 115 VAC		40 A max.
Input Protection			T 3.15 A / 250 VAC (Internal Fuse in L)
Recommended Input Fuse			3'150 mA (slow blow) (The need of an external fuse has to be assessed in the final application.)

Output Specifications

Voltage Set Accuracy			±2% max.
Regulation	- Input Variation (Vmin - Vmax)		0.5% max.
	- Load Variation (10 - 100%)		3% max.
Ripple and Noise (20 MHz Bandwidth)		12 VDC model:	120 mVp-p typ. (w/ 10 µF Alu || 0.1 µF MLCC)
		15 VDC model:	150 mVp-p typ. (w/ 10 µF Alu || 0.1 µF MLCC)
		24 VDC model:	240 mVp-p typ. (w/ 10 µF Alu || 0.1 µF MLCC)
		36 VDC model:	360 mVp-p typ. (w/ 10 µF Alu || 0.1 µF MLCC)
		48 VDC model:	480 mVp-p typ. (w/ 10 µF Alu || 0.1 µF MLCC)
		56 VDC model:	560 mVp-p typ. (w/ 10 µF Alu || 0.1 µF MLCC)
Capacitive Load		12 VDC model:	4'600 µF max.
		15 VDC model:	3'300 µF max.
		24 VDC model:	1'800 µF max.
		36 VDC model:	1'060 µF max.
		48 VDC model:	500 µF max.
		56 VDC model:	360 µF max.
Minimum Load			Not required
Temperature Coefficient			±3 %/K max.
Hold-up Time	- At 230 VAC		60 ms min.
	- At 115 VAC		15 ms min.
Start-up Time	- At 230 VAC		1.5 s max.
	- At 115 VAC		3 s max.
Short Circuit Protection			Continuous, Automatic recovery
Output Current Limitation			110 - 200% of Iout max.
Overvoltage Protection			110 - 170% of Vout nom. (Latch mode)
Transient Response	- Response Deviation		3% typ. / 5% max. (50% to 75% Load Step)
	- Response Time		1 ms typ. / 1.5 ms max. (50% to 75% Load Step)

Safety Specifications

Standards	- IT / Multimedia Equipment	EN 62368-1 IEC 62368-1 UL 62368-1
	- Certification Documents	www.tracopower.com/overview/txo60
Protection Class		Class I & II (Prepared): Reinforced Insulation
Pollution Degree		PD 2
Over Voltage Category		OVC II

All specifications valid at 230 VAC, resistive full load and +25°C after warm-up time, unless otherwise stated.

Downloaded from Arrow.com.

EMC Specifications

EMI (Emissions)	- Conducted Emissions		EN 55032 class B (internal filter) FCC 47 Part 15 class B (internal filter)
	- Radiated Emissions		EN 55032 class B (internal filter) FCC 47 Part 15 class B (internal filter)
	- Harmonic Current Emissions		EN 61000-3-2, class A
	- Voltage Fluctuations & Flicker		EN 61000-3-3
EMS (Immunity)			EN 55035 (Multimedia)
	- Electrostatic Discharge	Air:	EN 61000-4-2, ±8 kV, perf. criteria A
		Contact:	EN 61000-4-2, ±4 kV, perf. criteria A
	- RF Electromagnetic Field		EN 61000-4-3, 3 V/m, perf. criteria A
	- EFT (Burst) / Surge		EN 61000-4-4, ±1 kV, perf. criteria A
		L to L:	EN 61000-4-5, ±1 kV, perf. criteria A
	- Conducted RF Disturbances		EN 61000-4-6, 3 Vrms, perf. criteria A
	- PF Magnetic Field	Continuous:	EN 61000-4-8, 1 A/m, perf. criteria A
	- Voltage Dips & Interruptions	230 VAC / 50 Hz:	EN 61000-4-11 30%, 25 periods, perf. criteria A >95%, 0.5 periods, perf. criteria A >95%, 250 periods, perf. criteria B
EMC / Environmental	- Certification Documents		www.tracopower.com/overview/txo60

General Specifications

Relative Humidity			95% max. (non condensing)
Temperature Ranges	- Operating Temperature		−20°C to +70°C
	- Approved Ambient Temp.		+70°C max. (for 50% load) +50°C max. (for 100% load) (for compliance to 62368-1)
	- Storage Temperature		−40°C to +85°C
Power Derating	- High Temperature		2.5 %/K above 50°C
	- Low Input Voltage		2 %/V below 90 VAC
		See application note:	www.tracopower.com/overview/txo60
Cooling System			Natural convection (20 LFM)
Altitude During Operation			2'000 m max.
Regulator Topology			Flyback Converter
Switching Frequency			65 kHz typ. (PWM)
Insulation System			Reinforced Insulation
Working Voltage (rated)			576 VAC
Isolation Test Voltage	- Input to Output, 60 s		3'000 VAC (4'242 VDC)
Creepage	- Input to Output		6 mm min.
Clearance	- Input to Output		6 mm min.
Isolation Resistance	- Input to Output, 500 VDC		100 MΩ min.
Leakage Current (at 264 VAC / 60 Hz)	- Touch Current		100 µA max.
Reliability	- Calculated MTBF		100'000 h (MIL-HDBK-217F, ground benign)
Washing Process			Not allowed
Environment	- Vibration		2.4 g, 3 axis, random waveform, 30 min
	- Mechanical Shock		20 g, 3 axis, 6 shocks
Housing Type			Open Frame
Mounting Type			Chassis Mount
Connection Type			Pin Connector
Weight			120 g

All specifications valid at 230 VAC, resistive full load and +25°C after warm-up time, unless otherwise stated.

Downloaded from Arrow.com.

Environmental Compliance	- REACH Declaration	www.tracopower.com/info/reach-declaration.pdf REACH SVHC list compliant REACH Annex XVII compliant
	- RoHS Declaration	www.tracopower.com/info/rohs-declaration.pdf Exemptions: 7a (RoHS exemptions refer to the component concentration only, not to the overall concentration in the product (O5A rule).)
	- SCIP Reference Number	c09fb5a7-398c-470a-aee2-dc5745c093f7

Supporting Documents

Overview Link (for additional Documents)	www.tracopower.com/overview/txo60

Outline Dimensions



Dimensions in mm (inch)
General tolerances: ±0.5 (±0.02)
Mounting screw tightening torque: 0.59 Nm max. (6.0 kgfcm max.)

Pin connectors

Input (CN1)		Output (CN2)	
Pin	**Function**	**Pin**	**Function**
1	AC (L)	**1**	–Vout
3	AC (N)	**2**	
		3	+Vout
		4	

Input: JST series, B3P-VH(LF)(SN), 3.96mm
mates with JST crimp terminal: SVH-21T-P1.1 or equivalent
and terminal housing: VHR-3N or equivalent

Output: JST series, B4P-VH(LF)(SN), 3.96mm
mates with JST crimp terminal: SVH-21T-P1.1 or equivalent
and terminal housing: VHR-4N or equivalent

© Copyright 2025 Traco Electronic AG

Downloaded from Arrow.com.